

Tech Check List

ALL MACHINES	☐ Are plates securely mounted? See rule book
□AXLES: Cotter pin or safety wired?	Appendix A.
□ BODY WORK: Secured?	\Box Is number surface relatively flat and 10" X 12"?
☐ AFM legal belly pan? (Required for all 4-stroke bikes)	☐ Are number legible? See rule book Appendix A
□Lights taped over or removed?	\Box Is the number on the bike your AFM number?
□BRAKES, FRONT/REAR (as applicable)	□SCORING TRANSMITTER: All bikes must have
☐Brake caliper bolts: safety wired or mechanical	an AFM scoring transmitter at all times while
locking device?	on the track.
Anchor arm: safety wired or mechanical locking	☐ Is it mounted correctly?
device?	□CLEANLINESS: Is bike clean? Excessively oily?
☐ Actuating mechanism: operating properly?	□DRIVE CHAIN TENSION: OK?
☐Brake pads: in good shape and have enough	□CHAIN TENSION: adjusters tightened?
material?	☐MASTER LINK: clip mounted correctly and in good
Cables and hoses: in good shape?	shape? See rule book Appendix A
☐Brake fluid: level OK and cap tight?	□REAR WHEEL ALIGNMENT: OK? Wheels balanced?
SIDE CASES: See rule book Appendix A	□ SPOKED and MAG WHEELS: OK? No cracks? Spokes
□BELLY PANS: See rule book Appendix A	(if laced-up) tight?
□VENTED CATCH TANK: required for all overflows,	TIRES: OK? Steel valve caps on? Correct pressure in tires?
drains or breather tubes	□SHOCKS – REAR: Nuts, bolts and retainers OK?
□ CRANKCASE BREATHER TUBE: into catch tank or	□FRONT END: Triple clamp bolts tight? Steering damper
airbox	mounted correctly?
□OIL DRAIN PLUG, ENGINE: tight and safety wired?	☐ HANDLEBARS: Tank clearance OK? Tightened?
OIL FILTER: Secured with hose clamp and prevented from	ON/OFF SWITCH: Functioning?
spinning	PRODUCTION
□OIL PRESSURE SWITCH: have RTV securing it?	□Exhaust baffles wired?
OIL FILTER CAP: safety wired or clip allowed if properly	License bracket removed (if not part of tail light assembly)?
wired?	Stop light disabled?
□OIL LINE BOLTS: safety wired or RTV secured?	□All lenses taped?
	☐ Turn signals removed?
□BOLTS and HOSES TO OIL COOLER: safety wired? □WATER JACKET DRAIN BOLTS: safety wired?	☐ I drift signals femoved? ☐ Mirrors removed?
WATER JACKET DRAIN BOLTS: safety wired?	Center and side stands removed?
☐HOSE CLAMPS: safety wire is recommended	
□RADIATOR CAP: tight and safety wired or clip allowed if	RIDER
properly wired?	□SAFETY GEAR: See rule book Appendix A
	Helmet
RADIATOR FLUID: water or AFM-approved substances-	Leathers
no glycols allowed!	Boots
EXHAUST SYSTEM:	Gloves
☐ Header pipe fastening OK?	☐Back protector
Rear supports OK?	
Exhaust baffles: safety wired?	
Quiet enough? Noise limit is 101-103dB	Inspector
maximum NILIMPER DI ATES, all biles must beue aggregations	nispector
□NUMBER PLATES: all bikes must have appropriate	

number plates, rule 8.2.1.

form rv:2009